

DIVERTER AND CHECK VALVES – 1-1/2" AND 2"

2-WAY, 3-WAY AND CHECK



263028



263029



263042

Featured Highlights

- Maintenance-free PTFE coated diverter seal
- Optimum positive-seal
- High Flow Rate
- Fiberglass reinforced handle
- Withstands pressure up to 1MPa.
- Chemical-resistant
- Used for diverting, shut-off or mixing applications
- Accepts 40mm, 50mm and 65mm PVC plumbing
- Field-adjustable stop positions
- Plumbed with inlet at any port
- Designed to work with most industry standard actuators

Ordering Information

Product	Description	Carton Qty.	Carton Wt. (kg)
2-WAY AND 3-WAY DIVERTER VALVES			
263028	3-Way PVC 50mm/2" (65mm/2-1/2" slip outside)	12	6
263029	2-Way PVC 50mm/2" (65mm/2-1/2" slip outside)	12	6
263037	3-Way PVC 40mm/1-1/2" (50mm/2" slip outside)	12	6
263038	2-Way PVC 40mm/1-1/2" (50mm/2" slip outside)	12	6
263047	3-Way Solar Valve w/ drain-down, CPVC 2 in. (2-1/2 in. slip outside)	12	6
CHECK VALVES			
263042	Check Valve CPVC 50mm/2" (65mm/2-1/2" slip outside)	12	6
702480	Check Valve CPVC 40mm/1-1/2" (50mm/2" slip outside)	12	6
R172288	Check Valve (Rainbow) Corrosion Resistant 40mm/1-1/2"	12	4
VALVE ACTUATORS			
263043	Valve Actuator CVA-24L 90 Degree	8	8
263044	Valve Actuator CVA-24Y 120 Degree	8	8
263045	Valve Actuator CVA-24T 180 Degree	8	8



263045