

PRO SERIES COMMERCIAL SWC

COMMERCIAL SALT WATER CHLORINATOR



FEATURED HIGHLIGHTS:

- Low energy use.
- Huge range of salt operation: 2000-35,000ppm (0.2% - 3.5%).
- Reverse-polarity self cleaning.
- Low operating temperature.
- Long life cell.
- Premium grade titanium cell.
- Computer control.
- Easy and intuitive digital display.
- Water flow and gas accumulation protection.
- Overload, short circuit and high temperature protection.
- Optional pH/ORP control.
- 1 year commercial warranty.

Pentair's PRO series commercial salt chlorinators are available for chlorine production from 100-1000g/hr. Suitable for medium and large public swimming pools that demand high output and reliable chlorine production. They feature a modular electrode design and intuitive

digital control that incorporates an LCD screen with userfriendly menus, alarms, data logging, water temperature monitoring, water flow monitoring, drive temperature, cabinet temperature and the possibility of sensor control.

ORDERING INFORMATION

| Product | Description | Cl Output (g/hr) | Cal. Hypo Equiv. (65%) | Sod. Hypo. Equiv. (12.5%) | Supply Voltage (VAC) | Power (W) | Output Voltage (VDC) | Output Current (A) | Dimensions (mm) |
|--|--------------------------------|------------------|------------------------|---------------------------|----------------------|-----------|----------------------|--------------------|-----------------|
| PRO SERIES COMMERCIAL SALT CHLORINATORS | | | | | | | | | |
| SWC-PRO-100 | PRO Series Commercial SWC 100 | 100 | 155g | 0.8L | 230-240 | 550 | 22 | 25 | 250x308x89 |
| SWC-PRO-150 | PRO Series Commercial SWC 150 | 150 | 230g | 1.2L | 230-240 | 825 | 22 | 37.5 | 250x308x89 |
| SWC-PRO-200 | PRO Series Commercial SWC 200 | 200 | 310g | 1.6L | 230-240 | 932 | 28 | 33.3 | 400x342x318 |
| SWC-PRO-250 | PRO Series Commercial SWC 250 | 250 | 380g | 2.0L | 230-240 | 1300 | 28 | 45 | 740x400x310 |
| SWC-PRO-500 | PRO Series Commercial SWC 500 | 500 | 760g | 4.0L | 230-240 | 2600 | 28 | 45x2 | 740x400x310 |
| SWC-PRO-750 | PRO Series Commercial SWC 750 | 750 | 1.1kg | 6.0L | 230-240 | 3900 | 28 | 45x3 | 740x400x310 |
| SWC-PRO-1000 | PRO Series Commercial SWC 1000 | 1000 | 1.5kg | 8.0L | 230-240 | 5200 | 28 | 45x4 | 740x400x310 |

ACCESSORIES

SWC-KIT-PHCL Free chlorine probe, pH probe, solenoid dosing pump and cells.

SWC-KIT-TEMP Temperature probe kit.

SWC-KIT-SALT Salt sensor kit.

SWC-KIT-FLOW Flow Sensor Kit (PRO100 & PRO150)

*All dimensions in mm.